

The application of Inter-Vehicle Communication system to ITS

Lei Yan¹, Maria Kihl², Yuefeng Liu¹, Lina He¹

¹ Institute of Remote Sensing & Geographic Information System, Peking University, Beijing100871, P.R. China, lyan@pku.edu.cn

² Dept. of Communication Systems, Lund University, BOX 118, SE-221 00 Lund, Sweden, maria@telecom.lth.se

1. Introduction

Since the concept of ITS (Intelligent Transportation System) was put forward in 1991 by the U.S. Department of Transportation, it has been viewed as a promising way to tackle modern traffic problems. The creation of ITS depends on the integration of four components: travelers, control centers, intelligent vehicles and field infrastructure, which calls for effective communication architectures. To address the requests, U.S. came up with four communication systems as table 1: WAWC (Wide Area Wireless Communications), FFC (Fixed-point to Fixed-point Communications), IVC (Inter-vehicle Communications), and DSRC (Dedicated Short Range Communications). Among them, IVC is in the earliest research phase (US Department of Transportation, 1997).

Table 1. ITS Communication Architecture

	Travellers	Control Centres	Intelligent vehicles	Field infrastructure
Travellers	WAWC	FFC	WAWC	
Control Centers	FFC	FFC		FFC
Intelligent vehicles	WAWC		IVC	DSRC
Field infrastructure		FFC	DSRC	DSRC

Though many applications of IVC system have been identified, most researches have focused on the data transmission protocols (Kiyohito, 2001). On the other hand, how to further apply it to ITS, or the implementation of the application layer in the communication system, is rarely examined.

2. IVC

In an IVC system, vehicles form mobile ad-hoc networks and are communicated each other to get real time information, thus enable the driver to access information hard

acquired or measured by on-board sensors. The study of IVC systems can be dated back to the 1980's. Since then some techniques as Internet, wireless LANs and GPS were not available, most of the proposed solutions are outdated. Besides, the main objective of early research was to enable data transmission between two vehicles, multi-hop systems were excluded (Fujimoto and Nakagawa, 1998; Yashiro and Kondo, 1993).

Recent research classifies IVC systems as single-hop IVC system (SIVC) and multi-hop one (MIVC) by whether or not the information is retransmitted at intermediate hops. SIVC can be used for applications like collision avoidance; while MIVC is suitable for those with long range communications, such as traffic monitoring, route guidance, and so on.

An IVC system has some important features. First, since it is highly distributed, it is greatly resilient to disruption and able to provide reliable information services. Second, no infrastructure is required. All needs are some IVE (in-vehicle equipment): CPU, wireless transceiver, GPS, system interface, memory, map data and certain sensors (depend on different applications). Moreover, its low delay on information satisfies real time applications, e.g. safety ones.

3. Applications to ITS

The intelligence of a transport system lies both in intelligent infrastructure and intelligent vehicles.

3.1 Intelligent vehicle

An intelligent vehicle can provide various assistances to driver. For example, collision notification, road warning, route guidance are typical applications, where IVC system plays an important role. In these applications, cars may disseminate information about collision or bad road condition, or local traffic information to other cars in a predetermined ZOR(zone of relevance, the area a data package should be sent to), either in event driven mode or in period one. In a route guidance application, the area of ZOR can be much larger than the first two applications, so that each car gathers enough traffic information on different roads to enable real time route optimization.

3.2 Intelligent infrastructure

Intelligent infrastructure is designed to deal with problems as emergency management, freeway management, etc. Traffic data collection and its processing are usually involved to decision making. The accuracy and efficiency of data collection are essential, especially in the case of traffic flow management. Various approaches for traffic data collection have been proposed, including fixed vehicle detectors, videos and probe vehicles (or so-called floating cars). Here the application of vehicle detectors is limited due to high investment costs. Probe vehicles could be good complement for fixed detectors, but their effectiveness depends on the right choice of

the sampling area and sampling method.

Inter-vehicle communication, however, provides a new approach to the problem. In an IVC system, any vehicle equipped with IVE can work as a probe vehicle, without any other special equipment. It is due to the fact that each vehicle can receive real time data of the other vehicles like location, speed, acceleration. Thus it is capable of deducting accurate real time traffic information, at least within its vicinity. In a MIVC system, the known area can be large enough for traffic monitoring application. Then the information could be transmitted to roadside infrastructure or control centers for further data processing.

4. Key techniques

4.1 Data transmission protocol

As mentioned before, many efforts have been made in this area. Since there is no international standard yet, various schemes on each communication layers have been proposed. The choice of schemes usually depends on different applications, especially the routing and forwarding algorithm and the addressing strategy on the network layer.

4.2 Traffic modelling

Traffic modelling is crucial for a successful IVC application. A good model identifies necessary traffic parameters, including package contents to be transmitted among cars, transmission rate and frequency, ZOR and so on. Few work has been done in this area. Sihem and Mounir (2006) have made some efforts in similar sense, but only for collision warning application, which is far from enough. Most existing traffic modeling researches are for computer simulation purpose, like Victor and Benjamin (1994).

4.3 Data aggregation

An effective data aggregation strategy will not only decrease transmitted data volume and increase the network throughput, but also improve the accuracy and efficiency of the IVC system. For example, in an traffic monitoring application, the system concerns more about the speed of the traffic flow rather than a single car on that road segment. Here we propose a distributed segment-based data aggregation strategy which is employed by each car in the system.

4.4 Security and Privacy

It is essential to find the right balance between security and privacy of an IVC system once it becomes pervasive. However, very few papers have dicussed these issues, mostly for very specific problems (Hubaux and Capkun, 2004). More general security

architectures are needed.

5. Experiment

The above mentioned techniques will be applied to an IVC system to deliver a typical ITS application, dynamic route guidance. Due to the cost and difficulties involved in deploying large vehicular test beds, we will evaluate their performance via a wireless network simulator JiST/SWANS, along with a mobility module for vehicles on city streets, STRAW. Since this research is based on our former work in multicast IVC protocol, a distributed robust geocast protocol will be employed in the simulation.

5.1 JiST

JiST (Java in Simulation Time) is a Java-based discrete-event simulator that runs over a standard Java Virtual Machine (JVM). In JVM's execution model, referred to as actual time execution, the application progress and the passing time are independent. In order to execute applications with more predictable performance models, real time execution model is introduced, in which the program's progress is dependent on the passing time. In simulation time execution, however, the time progress depends on the application one. The model is especially useful for evaluating the application performance where the consumed time is a key index.

By simulation development in a JiST environment, we can write normal Java codes, while it takes strict control of the advanced time via the sleep(n) system call. In essence, every instruction takes zero time to process procedures except sleep, which advances the simulation clock forward by exactly n simulated time quanta (Rimon, 2004).

5.2 SWANS

SWANS is a Scalable Wireless Ad hoc Network Simulator built, which is based on the JiST platform, a general-purpose discrete event simulation engine (Rimon, 2004). In an IVC system, vehicles (nodes) communicating each other form a wireless ad hoc network. And SWANS contains software components to form complete wireless network configurations. Different amounts of mobile nodes can be placed on a field and form a network configured by SWANS. Various IVC protocols can be employed and tested in SWANS to improve the efficiency of data communication in the network.

Our former work focused on developing an efficient protocol for the IVC system, and a distributed robust geocast protocol has been implemented in SWANS, which constitutes the basis of this research (Joshi, 2006).

5.3 STRAW

STRAW (Street Random Waypoint) is a mobility model for vehicular ad hoc networks, which constrains node movement to streets defined by map data and limits their mobility according to vehicular congestion and simplified traffic control mechanisms (David and Fabian, 2005). As an add-on module to SWANS, STRAW makes the modeling of vehicles more accurate and realistic.

The delivery of the application, dynamic route guidance, involves a lot of interaction with both SWANS and this module.

6. Acknowledgements

We are grateful to Lund University and Beijing Key Lab of Spatial Information Integration and Its Applications for funding the co-research between Peking University and Lund University.

7. References

- US DEPARTMENT OF TRANSPORTATION, 1997. National ITS architecture communication document, <http://www.itsoverview.its.dot.gov>.
- KIYOHITO T., 2001, Applications of wireless communication technologies for Intelligent Transport Systems. *Wireless Personal Communications*, 17, pp. 343–353.
- FUJIMOTO N.; NAKAGAWA M., 1998, System performance of DS/SS inter-vehicle communication and ranging system under Rician fading channel. In *Proceedings of the 9th IEEE International Symposium on Personal, Indoor and Mobile Radio Communications*, pp. 476–480.
- YASHIRO T., KONDO T., YAGOME H., HIGUCHI M., MATSUSHITA Y., 1993, A network based on inter-vehicle communication. In *Proceedings of Intelligent Vehicles '93 Symposium*, pp. 345–350.
- SIHEM C., MOUNIR F., MICHAEL M., 2006, Traffic models for Inter-Vehicle Communications. In *Proceedings of the 2nd IEEE international conference on information & communication technologies: from theory to applications*, pp. 773-778.
- VICTOR S. F., BENJAMIN M., 1994, Traffic modelling for telecommunications networks. In *IEEE Communications Magazine*, pp. 70-81.
- HUBAUX, J.P., CAPKUN, S., JUN LUO, 2004, The security and privacy of smart vehicles. In *IEEE Security & Privacy Magazine*, vol. 2, pp. 49–55.
- RIMON BARR, 2004. JiST– Java in Simulation Time User Guide, <http://jist.ece.cornell.edu/docs.html>.
- Rimon B., 2004. SWANS– Scalable Wireless Ad hoc Network Simulator User Guide, <http://jist.ece.cornell.edu/docs.html>.
- JOSHI, H.P., 2006, Distributed robust geocast: A multicast protocol for inter vehicle communication, Master's thesis (North Carolina State University).

DAVID R. Choffnes and Fabián E. Bustamante, 2005, Modeling Vehicular Traffic and Mobility for Vehicular Wireless Networks, Technical Report WU-CS-05-03, Department of Computer Science, Northwestern University.

Biography

Yan Lei is the director of Beijing Key Lab of Spatial Information Integration & Its Applications, vice Chair of China Academy of Image Science & Technology and IEEE senior member. He received his PhD in Department of Precision Instruments and Mechanology in 1994 at Tsinghua University, China. Now he is a professor at the Institute of RS&GIS, Peking University in China. His main research focuses on photography and remote sensing imaging, navigation control and LBS (location based services).

Maria Kihl received her MSc in Computer Engineering in 1993 and her PhD in Telecommunications in 1999, both at Lund University, Sweden. She is currently an Associate Professor at the Department of Communication Systems at the same university. Her main research focus is performance modelling and analysis of distributed applications and server systems.